


Тип	Ø A mm	Ø B mm	Ø C mm	L mm	Тип цанги	Об/мин	Макс. мощность KW-S1	Мом. кручения Nm-S1	Жёсткость	
									Осевая N/µm	Радialная N/µm
PS RG-81-C	80		15	185	D 8	120000	2	0.15	20	22
PS RG-82-P	80	14	15	185		120000	2	0.15	20	22
PS RG-83-C	80		20	200	D 12	90000	2.5	0.2	46	48
PS RG-84-P	80	19	20	200		90000	2.5	0.2	46	48
PS RG-85-C	80		25	220	D 14	75000	3	0.4	52	54
PS RG-86-P	80	24	25	220		75000	3	0.4	52	54
PS RG-101-C	100		20	203	D 12	90000	4.5	0.5	46	48
PS RG-102-P	100	19	20	203		90000	4.5	0.5	46	48
PS RG-103-C	100		25	220	D 14	75000	5	0.65	52	54
PS RG-104-P	100	24	25	220		75000	5	0.65	52	54
PS RG-105-C	100		30	235	D 16	60000	6	0.9	65	68
PS RG-106-P	100	28	30	235		60000	6	0.9	65	68
PS RG-121-C	120		25	250	D 14	75000	5	0.65	52	54
PS RG-122-P	120	24	25	250		75000	5	0.65	52	54
PS RG-123-C	120		30	265	D 16	60000	7	1.2	65	68
PS RG-124-P	120	28	30	265		60000	7	1.2	65	68
PS RG-125-C	120		30	290	D 20	45000	8.5	1.8	65	68
PS RG-126-P	120	28	30	290		45000	8.5	1.8	65	68
PS RG-151-C	150		30	300	D 20	45000	8.5	1.8	65	68
PS RG-152-P	150	28	30	300		45000	8.5	1.8	65	68
PS RG-153-C	150		35	320	D 24	30000	12	3.8	83	86
PS RG-154-P	150	33	35	320		30000	12	3.8	83	86
PS RG-155-C	150		45	350	HSK C 40	24000	20	7.9	98	130
PS RG-156-P	150	43	45	350		24000	20	7.9	98	130
PS RG-171-C	170		50	365	HSK C 50	18000	30	16	107	162
PS RG-172-P	170	48	50	365		18000	30	16	107	162
PS RG-173-C	170		65	380	HSK C 63	12000	32	25	130	225
PS RG-174-P	170	63	65	380		12000	32	25	130	225



**Контакты:**  
 ООО "СервоКИП"  
 603022, г. Нижний Новгород  
 ул.Тимирязева 15  
 (831) 433-23-01, 433-04-81  
 info@servokip.ru  
 www.servokip.ru